

HEED3 is now available in a Swiftwater Breathing Apparatus (SWBA®) package, ideal for first responders working in and around flood and swiftwater. HEED3 is one of the first type-approved SWBA® devices under the global *Good Practice Guideline*. This lightweight system connects to most PFDs to provide an on-demand air supply to provide respiratory protection at the surface and minimise inhalation or ingestion of contaminants.

WHY USE SWBA®?

According to NFPA, a firefighter is **four times more likely to lose their life in a water rescue** than in structural firefighting. SWBA® provides operators a new level of safety.



More Air

3 cu ft / 85lt of air gives approximately 57 breaths of air. At surface level, this can last several minutes.




Less Risk

Minimizes inhalation and ingestion of flood water contaminants.



More Time

Provides more window of time to survive, be rescued or carry out critical tasks.







- HEED3-SWBA®
 - 3 cu ft / 85 lt aluminum cylinder
 - o 27" flexible braided hose
 - 1st and 2nd Stage Regulators
- SWBA® Mounting System
- SWBA® Velcro Patch

- DOT 3AL 3000 or CE marked cylinder
- SCUBA (Yoke) cylinder fill adapter
- SCBA (DIN) cylinder fill adapter
- Low volume mask
- Type-approved hand-pump
- Portable electric compressors
- Nose clip (with lanyard)

SPECIFICATIONS

Service Pressure: 3000 PSI / 207 Bar

Regulator: Piston, downstream demand valve

Operational Temperature:-22°F / -30°C < +158°F / +70°C

Weight: 2.2 lbs. /1 kg (excluding mounting system)
Length: 9.75" / 25cm (excluding hose and mounting system)
Diameter: 2.25" / 5.7cm (excluding mounting system)

Pressure Relief: Integrated in regulator.





HEED3 SWBA® Training

SWBA® Awareness, Operator, Specialist and Instructor training available through

www.swba.tech



User Guides

User guides and service manuals are available from our website www.heed3.com

